

Dynamic UIs

Justin Post

Recap

ui

- Controls layout of app
- Basic layout uses a sidebar panel and a main panel
 - `bslib::page_sidebar()` or `shiny::sidebarLayout()`
- Use strings, formatted (html style) text, widgets (*Input functions), and output from server (*Output functions)

server

- Back-end for app
- Create outputs that react to inputs (must be a reactive context!)
 - `render*` functions, `reactive()`, and `reactiveValues()`
 - `observe()`, `observeEvent()`, and `eventReactive()`

Dynamic UI

- Often want to update UI based on user input!
- Methods for updating UI
 - `update*` functions
 - `renderUI()/uiOutput()`
 - `conditionalPanel()`

Using update* Functions

- Every input widget has a corresponding update function
 - `updateActionButton()`
 - `updateCheckboxInput()`
 - `updateNumericInput()`
 - `...`

Using update* Functions

- Every input widget has a corresponding update function
 - updateActionButton()
 - updateCheckboxInput()
 - updateNumericInput()
 - ...
- Requires session argument on server() function

```
server <- function(input, output, session) {  
  ---# do stuff  
}
```

- After all observers (reactive things) evaluate, updater sends message back to client

Using update* Functions

- Syntax of update* functions similar to the functions that created the inputs

```
numericInput(inputId,  
            label,  
            value,  
            min = NA,  
            max = NA,  
            step = NA,  
            width = NULL)
```

```
updateNumericInput(session,  
                  inputId,  
                  label = NULL,  
                  value = NULL,  
                  min = NULL,  
                  max = NULL,  
                  step = NULL)
```

Using update* Functions

- Syntax of `update*` functions similar to the functions that created the inputs
- Any arguments with `NULL` values ignored
- For `radioButtons()`, `checkboxGroupInput()`, and `selectizeInput()`, the set of choices can be cleared by using `choices = character(0)`

updateSliderInput() (First Attempt)

```
ui <- fluidPage(  
  ...  
  sidebarPanel(  
    sliderInput("bins", "Number of bins:",  
               min = 1, max = 50, value = 30),  
    numericInput("maxBins", label = "Set Maximum Number of Bins",  
               value = 50, min = 1, max = 100)  
  ...  
)  
  
server <- function(input, output, session) {  
  ...  
  updateSliderInput(session, "bins", max = input$maxBins)  
}
```

What is our issue?

updateSliderInput() (Fixed)

```
ui <- fluidPage(  
  ...  
  sidebarPanel(  
    sliderInput("bins", "Number of bins:",  
               min = 1, max = 50, value = 30),  
    numericInput("maxBins", label = "Set Maximum Number of Bins",  
               value = 50, min = 1, max = 100)  
  ...  
)  
server <- function(input, output, session) {  
  ...  
  observe({  
    updateSliderInput(session, "bins", max = input$maxBins)  
  })  
}
```

update* UI Functions

- Use the template app
- Try to add a numeric input for the user to specify the largest value of the slider
- Use the `updateSliderInput` function to update the max of the slider
- Add an `actionButton` to only update when pressed (so no intermediate updates while typing)

renderUI() and uiOutput()

- renderUI() and uiOutput() allow for flexible dynamic UI elements
- Recall: Shiny essentially writes HTML/JavaScript for us!

```
print(fluidPage(titlePanel(title = "Hi"),
                 sidebarLayout(sidebarPanel(), mainPanel())))

## <div class="container-fluid">
##   <h2>Hi</h2>
##   <div class="row">
##     <div class="col-sm-4">
##       <form class="well" role="complementary"></form>
##     </div>
##     <div class="col-sm-8" role="main"></div>
##   </div>
## </div>
```

renderUI() and uiOutput()

- renderUI() and uiOutput() allow for flexible dynamic UI elements
- Recall: Shiny essentially writes HTML/JavaScript for us!

```
print(numericInput("id", "Label User Sees", value = 10))

## <div class="form-group shiny-input-container">
##   <label class="control-label" id="id-label" for="id">Label User Sees</label>
##   <input id="id" type="number" class="shiny-input-number form-control" value="10"/>
## </div>
```

`renderUI()` and `uiOutput()`

- `renderUI()` makes a **reactive version** of a function that generates HTML!
- Can have `renderUI()` return
 - A widget or other function that makes HTML
 - A shiny 'tag object' created via `shiny::tagList()`
- Use with `uiOutput()` in UI file

renderUI() and uiOutput() (updating a widget)

```
ui <- fluidPage(  
  ...  
  sidebarPanel(  
    uiOutput("slider"),  
    numericInput("maxBins", label = "Set Maximum Number of Bins",  
               value = 50, min = 1, max = 100)  
  ...  
  server <- function(input, output, session) {  
    ...  
    output$slider <- renderUI({  
      sliderInput("bins", "Number of bins:", min = 1,  
                 max = input$maxBins, value = 30)  
    })  
  }  
}
```

renderUI() and uiOutput() (outputting HTML)

```
ui <- fluidPage(  
  ...  
  sidebarPanel(  
    uiOutput("info"),  
    numericInput("purchase", label = "How Many?",  
                value = 50, min = 0, max = 100)  
  ...  
server <- function(input, output, session) {  
  ...  
  output$info <- renderUI({  
    text <- paste0("You have selected to buy ", input$purchase)  
    h3(text)  
  })  
}
```

renderUI() and uiOutput() (using tagList())

```
ui <- fluidPage(  
  ...  
  sidebarPanel(  
    uiOutput("info"),  
    numericInput("purchase", label = "How Many?",  
                value = 50, min = 0, max = 100)  
,  
  ...  
,  
  server <- function(input, output, session) {  
  ...  
    output$info <- renderUI({  
      text <- paste0("You have selected to buy ", input$purchase)  
      slidey <- sliderInput("bins", "Number of bins:", min = 1,  
                            max = input$maxBins, value = 30)  
      tagList(  
        h3(text),  
        slidey  
      )  
    })  
  }  
}
```

`renderUI()` and `uiOutput()`

- Use the template app
- Try to add some dynamic updating text and things to the UI

conditionalPanel()

- Create a 'panel' that is only visible if a condition is met
- Condition can depend on input widget
 - Accessed differently! (Use a '.' not a '\$' and javascript style comparisons)

conditionalPanel()

```
...
sidebarPanel(
  selectInput("plotType", "Plot Type",
    c(Scatter = "scatter", Histogram = "hist")),

  # Only show this panel if the plot type is a histogram
  conditionalPanel(condition = "input.plotType == 'hist'",
    selectInput("breaks", "Breaks",
      c("Sturges", "Scott", "Freedman-Diaconis", "[Custom]" = "custom"))),
  # Secondary conditonalPanel, Only show this panel if Custom is selected
  conditionalPanel(
    condition = "input.breaks == 'custom'",
    sliderInput("breakCount", "Break Count", min = 1, max = 200, value = 40)
  )
)
)
```

conditionalPanel()

- Use the template app
- Try to add a new UI element using a conditional panel!

Dynamic UI Recap

- Often want to update UI based on user input!
- Methods for updating UI
 - `update*` functions
 - `renderUI()/uiOutput()`
 - `conditionalPanel()`